



- The work area is directly blown with HEPA filtered air at 99.99% efficent for 0.3 micron particulates.
- The work surface and the backwall are constructed with 304 stainless steel for durability and easy cleaning.
- Work-Stage can be taken apart without any tools for Cleaning.
- Equipped with Air velocity sensor which indicates the replacement of the HEPA filter.
- The HEPA filtered air directed vertically across the work surface. Positive pressure, unidirectional laminar airflow prevents any inflow of room air contaminants onto the work surface.

Options

- Variable Air Velocity Contorol
- Stage Warmer

(unit=mm)

| Models | | | | | | | | | | |
|-------------------------|--------|---|----------|----------|----------|----------|---|----------|----------|-----------|
| | | AH-100 | AH-130 | AH-160 | AH-180 | AH-200 | AH-130W | AH-160W | AH-205W | AH-205WS |
| Outer Dimensions | Height | 1920 | | | | | 1850 | | | |
| | WxD | 1000×750 | 1300×750 | 1600×750 | 1800×750 | 2000×750 | 1300×750 | 1600×750 | 2050×750 | 2050×1000 |
| Work Area Dimensions | Height | 750 | | | | | 750 | | | |
| | WxD | 950×610 | 1250×610 | 1550×610 | 1750×610 | 1950×610 | 1025×690 | 1325×690 | 1550×690 | 1550×940 |
| Air Flow Method | | Vertical Circulation | | | | | Vertical Circulation | | | |
| Exhaust Filter | | W305xD305xH65 | | | | | W305xD305xH65 | | | |
| HEPA Filter Efficiency | | 99.99% efficent for 0.3 micron particulates | | | | | 99.99% efficent for 0.3 micron particulates | | | |
| Weight | | 200kg | 260kg | 300kg | 335kg | 365kg | 230kg | 270kg | 320kg | 350kg |
| Power | | AC110V~220V 50/60Hz | | | | | | | | |